

TIRE AND WHEEL

SERVICE DATA

Cold tire inflation pressure	P215/70R15 97S	Front wheel	200 kPa (2.0 kgf/cm ² , 29 psi)
		Rear wheel	220 kPa (2.2 kgf/cm ² , 32 psi)
		Spare wheel	220 kPa (2.2 kgf/cm ² , 32 psi)
	P255/45R18 99V	Front wheel	240 kPa (2.4 kgf/cm ² , 35psi)
		Rear wheel	240 kPa (2.4 kgf/cm ² , 35psi)
		Spare wheel	240 kPa (2.4 kgf/cm ² , 35psi)
	P245/75R16 109S	Front wheel	200 kPa (2.0 kgf/cm ² , 29 psi)
		Rear wheel	200 kPa (2.0 kgf/cm ² , 29 psi)
		Spare wheel	200 kPa (2.0 kgf/cm ² , 29 psi)
	P265/70R16 111T	Front wheel	200 kPa (2.0 kgf/cm ² , 29 psi)
		Rear wheel	220 kPa (2.2 kgf/cm ² , 32 psi)
		Spare wheel	220 kPa (2.2 kgf/cm ² , 32 psi)
	P265/65R17 110S	Front wheel	200 kPa (2.0 kgf/cm ² , 29 psi)
		Rear wheel	200 kPa (2.0 kgf/cm ² , 29 psi)
		Spare wheel	200 kPa (2.0 kgf/cm ² , 29 psi)
Tire runout			3.0 mm (0118 in.) or less
Imbalance after adjustment			8 g (0.018 lb) or less

TORQUE SPECIFICATIONS

Part Tightened	N*m	kgf*cm	ft.*lbf
Tire pressure warning antenna and receiver x Body	5.0	51	44 in.*lbf
Battery negative terminal x Battery	3.9	40	35 in.*lbf
Tire pressure warning valve and transmitter x Wheel	4.0	41	35 in.*lbf
Front wheel	113	1,152	83
Rear wheel	113	1,152	83
Tire pressure warning ECU x Body	5.5	56	49 in.*lbf

SS